



DATASHEET SẠC DC - EVEREV

Stt	Công suất/Mã hàng	Hình ảnh	Thông số KT	Bảo hành
1	<p>Công suất: 20 kW</p> <p>Mã hàng: EV – DC001</p>		<p>Specification AC Input: AC380V±15%,3P+N+PEAC,50Hz/60Hz Consumption : ≤2W Rated Power : 20KW Output Power: CCS1 or CCS2: 150Vdc–1000Vdc, 0~66.7A Efficiency: ≥94%</p> <p>Functions Emergency Stop Button,LED indicator,RFID,TouchScreen Standards: IEC61851-1, IEC61851-23</p> <p>Communication OCPP 1.6 Network: Ethernet/4G</p> <p>Environment Condition Application: Indoor/Outdoor Working Latitude: <2000m Working Temperature: -30℃~+55℃ Working Humidity: 5%~95% Protection Level: IP55 Cooling: Forced-air cooling</p>	<p>12 tháng</p>
Structure Description		Shell Material:Carbon Steel; Dimension:450*250*850(L *W*T); Weight:65kG; Installation:Wall-Mounted; Cable Length: 5 M		

Connector: DC*1; Screen: 9.1 inch LCD Screen

2

Công suất: 30 kW

Mã hàng: EV – DC002



Specification

AC Input: AC380V±15%,3P+N+PEAC,50Hz/60Hz

Consumption : ≤2W

Rated Power :30KW

Output Power:CCS1 or CCS2: 150Vdc–1000Vdc, 0~100A

Efficiency: ≥94%

Function

Emergency Stop Button,LED indicator,RFID,TouchScreen

Standards: IEC61851-1, IEC61851-23

Communication

OCPP 1.6

Network: Ethernet/4G

Environment Condition

Application place: Indoor/Outdoor

Working Latitude: <2000m

Working Temperature: -30℃~+55℃

Working Humidity: 5%~95%

Protection Level: IP55

Cooling: Forced-air cooling


12 tháng

Structure Description

Shell Material: Carbon Steel; Dimension:450*250*850(L *W*T); Weight:65kG; Installation:Wall-Mounted; Cable Length: 5 M

Connector: DC*1; Screen: 9.1 inch LCD Screen



3	<p>Công suất: 40 kW</p> <p>Mã hàng: EV – DC003</p>		<p>Specification</p> <p>AC Input: AC380V±15%,3P+N+PEAC,50Hz/60Hz</p> <p>Consumption : ≤2W</p> <p>Rated Power :40KW</p> <p>Output Power:CCS1 or CCS2: 150Vdc–1000Vdc, 0~133A</p> <p>Efficiency: ≥94%</p> <p>Functions</p> <p>Emergency Stop Button,LED indicator,RFID,TouchScreen</p> <p>Standards: IEC61851-1, IEC61851-23</p> <p>Communication</p> <p>OCPP 1.6</p> <p>Network: Ethernet/4G</p> <p>Environment Condition</p> <p>Application: Indoor/Outdoor</p> <p>Working Latitude: <2000m</p> <p>Working Temperature: -30℃~+55℃</p> <p>Working Humidity: 5%~95%</p> <p>Protection Level: IP55</p> <p>Cooling: Forced-air cooling</p>	<p>12 tháng</p>
<p>Structure Description</p>		<p>Shell Material: Carbon Steel; Dimension:450*250*850(L *W*T); Weight:65kG; Installation:Wall-Mounted; Cable Length: 5 M</p> <p>Connector: DC*1; Screen: 9.1 inch LCD Screen</p>		

Contact:

Head office: 300B Minh Khai, Minh Khai, Hai Ba Trung, Ha Noi, Viet Nam
 Technical hotline: 0912055752
 Email: everev.vn@gmail.com